

# HEAVY-DUTY LIFTS



Shown: Model CR40  
40,000 lbs. capacity

## CR40/50

- 40,000 lbs. / 50,000 lbs. capacity
- Locking latches in each leg
- 24" wide runways
- Low maintenance - proven durability
- Alignment designs available
- High capacity rolling jacks available

## CR60

- 60,000 lbs. capacity
- Locking latches in each leg
- 28" wide runways
- Special high capacity power units
- Alignment designs available
- High capacity rolling jacks available



Shown: Model CR60  
60,000 lbs. capacity

*Engineered to Perform...  
Built to Last*

## Engineering Excellence

Forward Lift products are *engineered to perform* and *built to last*. Forward's U.S. engineers have over 29 years of combined experience designing automotive lifts for service and repair shops. Forward's philosophy is to own our designs rather than use someone else's off the shelf product.

## Product Integrity

21st century design tools allow us to create, control and validate our designs to ensure maximum performance. Forward lifts are rigorously tested to meet quality and durability standards. All product families are proof load tested to 1½ times rated capacity and rigorously cycle tested.



**FORWARD<sup>®</sup> LIFT**  
A **DOVER<sup>™</sup>** COMPANY



Shown: Optional Rolling  
Bridge Jacks

### Available Options:

- Internal Air Line Kit
- Rolling Bridge Jacks
- Drive Through Ramps
- Power Unit Cover
- Mobile Oil Drain Pans
- Single and 3-Phase Motors
- Custom Colors

Specifications	CR40	CR50	CR60
Capacity	40,000 lbs. (18411kg)	50,000 lbs. (22680kg)	60,000 lbs. (27216kg)
Maximum Wheelbase	300" (7620mm)	360" (9144mm)	396" (10058mm)
Maximum 2-Wheel Align (with alignment kit)	270" (6858mm)	330" (8382mm)	366" (9296mm)
Lifting Height	68" (1727mm)	68" (1727mm)	68" (1727mm)
Overall Length	34'-4" (10465mm)	38'-10" (11836mm)	43'-10" (13360mm)
Overall Width	14'-3" (4343mm)	14'-3" (4343mm)	15'-6" (4877mm)
Width Inside Columns	11'-10" (3607mm)	11'-10" (3607mm)	12'-4" (3759mm)
Overall Height	12'-10" (3912mm)	12'-10" (3912mm)	13'-1" (3988mm)
Runway Width	24" (610mm)	24" (610mm)	28" (711mm)
Runway Height	9" (229mm)	9" (229mm)	12" (305mm)
Width Between Runways			
Amperage			
208/230v, Single-Phase	40 Amps	40 Amps	40 Amps
208/230v, Three-Phase	25 Amps	25 Amps	25 Amps
460v, Three-Phase	15 Amps	15 Amps	15 Amps
Motor	2 HP X 2	2 HP X 2	2 HP X 2

Specifications subject to change without notice or liability

Forward Lift  
996 Industrial Drive  
Madison, IN 47250  
Phone: 800.423.1722  
Fax: 812.273.7329

[www.forwardlift.com](http://www.forwardlift.com)

Lit# HeavyDuty\_2007.11

©2007 Forward®, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, FORWARD DOVER and all other trademarks are property of Dover Corporation and its affiliates.



**FORWARD LIFT**  
A DOVER COMPANY